Model identifier(s): Scar	n 83						
Indirect heating functionality				No			
Direct heat output(kW)				5			
Indirect heat output(kW)				N.A			
Fuel				Preferred fuel (only one) Model identifier(s)			
Wood logs with moisture content $\leftarrow$ 25%				Yes	No		
Compressed wood with moisture content < 12%				No	No		
Other woody biomass				No	No	No	
Anthracite and dry steam coal				No	No	No	
Hard coke				No	No	No	
Low temperature coke				No	No		
Bituminous coal				No	No		
Lignite briquettes				No	No	No	
Peat briquettes				No	No	No	
Blended fossil fuel briquettes				No	No	No	
Other fossil fuel				No	No	No	
Blended biomass and fossil fuel briquettes				No	No	No	
Other blend of biomass and solid fuel				No	No	No	
Characteristics when operating with the preferred fuel							
Seasonal space heating				72			
Energy Efficiency Class				A+			
Energy Efficiency Index (EEI)				108,5			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heat output	Зушвет	Value	Onte	<b>Use efficiency</b> (NCV as re		Value	Onte
Nominal heat output	P <sub>nom</sub>	5	kW	Useful efficiency at nominal heat output	$\eta_{th,nom}$	81	%
Minimum heat output (indicative)	$P_{min}$	N.A.	kW	Useful efficiency at minimum heat output (indicative)	η <sub>th, min</sub>	N.A.	%
Auxiliary electricity cons	sumption			Type of heat output/roo	om temperat	ure control (	select one
At nominal heat output	el <sub>max</sub>	x,xxx	kW	single stage heat output, no room temperature control		[yes/no]	select one
At minimum heat output	el <sub>min</sub>	x,xxx	kW	two or more manual stages, no room temperature control		[yes/no]	Yes
In standby mode	el <sub>sB</sub>	x,xxx	kW	with mechanic thermostat room temperature control		[yes/no]	
				with electronic room temperature control		[yes/no]	
				with electronic room temperature control plus day timer		[yes/no]	
				with electronic room temperature control plus week timer		[yes/no]	
				Other control options (r	nultiple selec	tions possible	
				room temperature cont presence detection	room temperature control, with presence detection		
				room temperature control, with open window detection		[yes/no]	
			with distance control option		[yes/no]		
Permanent pilot flame p	ower requir	ement					
Pilot flame power requirement (if applicable)	$P_{pilot}$	N.A.	kW		, /		
Contact details	Name and	address of	the supplie	V/1	D Manager, Scan	A/S, Denmark	